

ZQ-ANT-5

LTE antenna with bracket

Antenna omnidirezionale 4G-LTE/5G (Band 1, 2, 3, 5, 7, 8, 20, 28, 77, 78). Antenna con elementi radianti isolati rispetto all'esterno del radome dell'antenna ed a tenuta stagna (IP67), completa di cavo low-loss Ø5mm lunghezza 3m con conettore SMA-M e staffa per l'installazione a palo/muro.

4G-LTE/5G omnidirectional antenna (Band 1, 2, 3, 5, 7, 8, 20, 28, 77, 78). Antenna with radiating elements isolated from the outside of the antenna radome and watertight (IP67), complete with Ø5mm low-loss cable 3m long with SMA-M connector and bracket for pole/wall installation.



Modelli | Models

Model	Code	Description
ZQ-ANT-5	ZQ06-05R0	LTE antenna, IP67, low-loss 3m cable SMA-M and bracket.

Specifiche tecniche | Technical specifications

Frequency band (VSWR <2:1)	698-960/1710-2170/2400-2690/3300-3800 MHz
Impedance	50 Ω
V.S.W.R.	< 2 : 1
Max power	25 W
Polarization	Linear
Radiation	Omnidirectional
Gain	698-960 MHz: 2,1 dBi, 1710-2170 MHz: 3,5 dBi, 2400-2690 MHz: 4,5 dBi, 3300-3800 MHz: 4,5 dBi
Cable	Low-loss Ø5mm, 3m
Operating temperature	-30° / +80°C
Radiant element	Copper
Screws	Stainless steel
Connector	SMA male
IP grade	IP67
Dimensions (approx):	Ø16x82 mm
Weight (approx):	40 g

